

4CH H.264 Digital Video Recorder

# ACD1S0460



**Features:**

- 4ch D1 real-time DVR Video (H.264)
- Combined BNC and VGA video output for main display (up to 1280 x 1024)
- Up to 4ch audio inputs and 1ch audio output
- Support Windows\Symbian\ iPhone\Blackberry\Andriod OS
- Support 1 SATA HDD, Capacity to 2TB
- Remote Surveillance with Browsers and CMS

**Specifications**

MODEL	ACD1S0460	
DISPLAY		
Video	Inputs	4 Composite video
	Resolution	PAL: D1 (704x576), NTSC: D1 (704x480)
	Frame Rate	D1@100fps, HD1@100fps, CIF@100fps Adjustable
	Resolution	PAL: D1 (704x576), NTSC: D1 (704x480)
	Live Display picture	1/4
PERFORMANCE		
Operating System	Embedded	Linux
	DST	Support
	Multiplex Operation	Live\Display\Playback\Recording\Backup\Mobile Phone Surveillance \Network simultaneously
Recording	Compression	H.264
	Frame Rate	D1@100fps, HD1@100fps, CIF@100fps Adjustable
	Resolution	PAL: D1(704x576), HD1(704x288), CIF(352x288); NTSC: D1(704x480), HD1(704x240), CIF(352x240)
	Mode	Manual\Timer\Motion Detection\Alarm
	Overwrite Modes	Continuous
	Play	Special player, Support AVI file format conversion
	JPEG Capture function	Support, 3M Pixels@10fps
Playback		1/4 channels playback simultaneously (Optional playback channel)
	Transmission Speed	4 channels real-time network transmission with CIF resolution
Network	Dual Stream	Support (Main and secondary interchange)
	Max. Remote Users	Support maximum five users online access
	Protocol Support	Support TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, UPNP
	Internet Browser	IE, Firefox, Chrome
	Client Software	Support
	Mobile Phone Surveillance	Support Windows\Symbian\ iPhone\Blackberry\Andriod OS
Storage	Internal HDD	Support 1 SATA HDD, Capacity to 2TB
	Backup	USB, Moved Hard Disk, USB Writer, Network
Security	Password Protection	Yes
	Data Authentication	Watermark
INTERFACE		
Monitor	VGA	1 channel 800x600, 1024x768, 1280x1024 resolution
	Main Composite	1 channel BNC
Audio	Input	4 Channels RCA
	Output	1 Channel RCA
Alarm	Input	4 Channels
	Output	1 Channel
Connections	Remote Notification	Send pieces to the designated email
	USB	USB2.0
	Application support	Mouse, Remote Controller, Panel Operating
	PTZ Control	RS-485
Communication Protocols	Ethernet	1 RJ-45 10/100Mbps Ethernet Connector
	PTZ	Support PELCO-D & PELCO-P
GENERAL		
Electrical	Power	DC12V/3A
Environmental	Working Temperature	0°C-50°C
	Working Humidity	10% - 90%
Mechanical	Dimensions	354(W)×230(D)×45(H)
	Weight	4Kg
Language		Multi-Language

DISTRIBUTED BY

